

42. (AMENDED) A sensor according to claim 39 in which the fibre is under a first strain during inscription of the first part.

43. (AMENDED) A sensor according to claim 40 in which the fibre is under a first strain during inscription of the first part and is under a second strain during inscription of the second part, the first and second strains being different.

46. (AMENDED) A sensor according to claim 25 in which the optical fibre is photosensitive enhanced optical fibre.

48. (AMENDED) A sensor according to claim 46 in which the fibre is hydrogen loaded to increase the photosensitivity of the fibre.

50. (AMENDED) A sensor according to claim 1 in which the grating portion comprises a surface-relief grating structure side-etched in an optical fibre.

51. (AMENDED) A sensor according to claim 25 in which the fibre grating sensor comprises a plurality of grating portions.

54. (NEW) A sensor according to claim 25 in which the grating portion comprises a surface-relief grating structure side-etched in an optical fibre. --

REMARKS

This preliminary amendment is presented prior to examination of the above-identified application filed pursuant to 35 USC §371 based on PCT/GB00/00496. No new matter is believed added by these claim amendments which are presented purely for clarity purposes only; no limiting of the claimed subject matter is to be inferred from the amendments.


Applicants have made a diligent effort to place the claims in condition for allowance. However, should there remain unresolved issues that require adverse action, it is respectfully requested that the Examiner telephone, Applicants' Attorney at (203) 972-0081 so that such issues may be resolved as expeditiously as possible.

For these reasons, and in view of the above amendments, this application is now considered to be in condition for allowance and such action is earnestly solicited.

Respectfully Submitted,

August 15, 2001

Date



Kurt M. Maschoff

Reg. No. 38, 235

Attorney for Applicants

Buckley, Maschoff, Talwalkar & Allison LLC

111 Elm Street

New Canaan, CT 06840

(203) 972-0081/voice

(203) 972-7627/fax

APPENDIX A—CLAIM AMENDMENTS

1. A fibre optic grating sensor comprising an optical fibre having a grating portion along which the refractive index of the fibre varies periodically, the periodic variation having an amplitude envelope which includes at least one region in which the amplitude of the envelope is substantially reduced, the said variation giving the grating portion a spectral profile within which there is at least one pass band.
2. A sensor according to claim 1 in which the amplitude envelope includes a plurality of regions in which the amplitude of the envelope is substantially reduced.
3. A sensor according to claim 2 in which the amplitude envelope includes a plurality of regions in which the amplitude of the envelope is substantially nulled.
4. (AMENDED) A sensor according to claim 2 [or 3] in which the periodic variation in the or each region includes a section in which the phase of the periodic variation substantially reverses.
5. (AMENDED) A sensor according to [any of] claim[s] 2 [to 4] in which adjacent regions are spatially separated.
6. (AMENDED) A sensor according to [any preceding] claim 2 in which the or each region gives rise to a corresponding pass band.
7. A sensor according to claim 6 in which each region is an independently actuatable sensor element operable to vary the wavelength of the corresponding pass band in response to a change in a parameter being measured.
8. (AMENDED) A sensor according to [any preceding] claim 1 in which the grating portion comprises two substantially superimposed fibre Bragg gratings.

9. A sensor according to claim 8 in which the amplitudes of the refractive index profiles of the two gratings add together to form the amplitude envelope.
10. (AMENDED) A sensor according to claim 8 [or 9] in which the fibre Bragg gratings are chirped fibre Bragg gratings.
11. A sensor according to claim 10 in which the two chirped gratings have substantially the same rate of chirp and substantially the same spectral bandwidth, the first chirped grating having a different central wavelength to the second chirped grating.
12. A sensor according to claim 10 in which the first chirped grating has a different rate of chirp to the second chirped grating, and the two chirped gratings have substantially the same central wavelength and bandwidth.
13. (AMENDED) A sensor according to claim 8 [or 9] in which the fibre Bragg gratings are linear fibre Bragg gratings.
14. A sensor according to claim 13 in which the two linear gratings have substantially the same spectral bandwidth.
15. A sensor according to claim 14 in which the first linear grating has a different central wavelength to the second linear grating.
16. (AMENDED) A sensor according to [any of] claim[s] 1 [to 7] in which the grating portion comprises one fibre Bragg grating having a plurality of regions within which the refractive index profile of the grating is substantially reduced or nulled.
17. A sensor according to claim 16 in which the fibre Bragg grating is a linear grating or a chirped grating.
18. (AMENDED) A sensor according to [any of] claim[s] 8 [to 17] in which the or each fibre Bragg grating is fabricated using a two-beam interference holographic fabrication method.
19. (AMENDED) A sensor according to [any of] claim[s] 8 [to 17] in which the or each fibre Bragg grating is fabricated using a phase-mask fabrication method.

20. (AMENDED) A sensor according to claim 18 [when dependent on claim 16 or 17] in which the or each region in the fibre Bragg grating is formed in a fibre Bragg grating fabricated using the two-beam interference holographic fabrication method by providing an amplitude mask generally in front of the fibre, generally in the beam paths, during fabrication.
21. (AMENDED) A sensor according to claim 1[8]9 [or 19 when dependent on claim 16 or 17] in which the or each region in the fibre Bragg grating is formed in a fibre Bragg grating fabricated using one of the two-beam interference holographic fabrication method [or]and the phase-mask fabrication method by subsequently further exposing regions of the grating.
22. (AMENDED) A sensor according to [any of] claim[s] 1 [to 7] in which the grating portion comprises a single grating structure fabricated using a phase-mask fabrication method.
23. A sensor according to claim 22 in which the desired grating structure is represented on a phase-mask and subsequently inscribed into the fibre through the phase-mask.
24. A sensor according to claim 22 in which the grating structure is inscribed in the fibre through a phase-mask while the fibre undergoes oscillating motion along its longitudinal direction, relative to the phase-mask, to thereby control the refractive index profile within the grating structure.
25. A fibre optic grating sensor comprising an optical fibre having a grating portion along which the refractive index of the fibre varies periodically, the periodic variation including at least one section in which the phase of the periodic variation substantially reverses, the said variation giving the grating portion a spectral profile within which there is at least one pass band.
26. A sensor according to claim 25 in which the grating portion includes a plurality of sections in which the phase of the periodic variation substantially reverses.
27. A sensor according to claim 26 in which adjacent phase reversal sections are spatially separated.

28. (AMENDED) A sensor according to [any of] claim[s] 26[25 to 27] in which the or each phase reversal section gives rise to a corresponding pass band.
29. A sensor according to claim 28 in which each section is an independently actuatable sensor element operable to vary the wavelength of the corresponding pass band in response to a change in a parameter being measured.
30. (AMENDED) A sensor according to [any of] claim[s] 25 [to 29] in which the period of the periodic variation changes along substantially the full length of the grating portion.
31. (AMENDED) A sensor according to [any of] claim[s] 25 [to 30] in which the grating portion comprises two substantially overlapping chirped fibre Bragg gratings, the first chirped grating being spatially shifted relative to the second chirped grating by an integer plus a fraction of the period of the first grating.
32. A sensor according to claim 31 in which the first chirped grating is spatially shifted relative to the second chirped grating by an integer plus one half of the period of the first grating.
33. (AMENDED) A sensor according to claim 31 [or 32] in which the two chirped gratings have substantially the same rate of chirp and substantially the same spectral bandwidth, the first chirped grating having a different central wavelength to the second chirped grating.
34. (AMENDED) A sensor according to claim 31 [or 32] in which the first chirped grating has a different rate of chirp to the second chirped grating, and the two chirped gratings have substantially the same central wavelength and bandwidth.
35. (AMENDED) A sensor according to any of claim[s] 31 [to 34] in which the fibre Bragg gratings are fabricated using a known two-beam interference holographic fabrication method.
36. (AMENDED) A sensor according to [any of] claim[s] 31 [to 34] in which the fibre Bragg gratings may be fabricated using a known phase-mask fabrication method.

37. (AMENDED) A sensor according to [any of] claim[s] 25 [to 30] in which the grating portion comprises one chirped fibre Bragg grating having a plurality of sections in which the phase of the periodic variation substantially reverses.

38. A sensor according to claim 37 in which the single chirped fibre Bragg grating is fabricated using a known phase-mask fabrication technique.

39. A sensor according to claim 38 in which a first part of the chirped grating having a first spectral bandwidth is represented on a phase-mask and subsequently inscribed into the fibre.

40. A sensor according to claim 39 in which a second part of the chirped grating having a second spectral bandwidth is inscribed into the fibre substantially spatially and spectrally adjacent the first part, the first and second parts together forming the chirped grating.

41. A sensor according to claim 40 in which the chirped grating comprises a plurality of such parts arranged substantially spatially and spectrally sequentially adjacent one another.

42. (AMENDED) A sensor according to [any of] claim[s] 39 [to 41] in which the fibre is under a first strain during inscription of the first part.

43. (AMENDED) A sensor according to claim [42]40 in which the fibre is under a first strain during inscription of the first part and is under a second strain during [subscription]inscription of the second part, the first and second strains being different.

44. A sensor according to claim 37 in which the chirped grating is fabricated using a single phase-mask, the desired structure of the chirped grating being represented on the phase-mask and subsequently inscribed into the fibre through the phase-mask.

45. A sensor according to claim 37 in which the chirped grating is fabricated using a known continuous writing technique.

46. (AMENDED) A sensor according to [any preceding] claim 25 in which the optical fibre is photosensitive enhanced optical fibre.

47. A sensor according to claim 46 in which the photosensitive enhanced optical fibre is germania doped optical fibre, or boron-germania co-doped optical fibre.

48. (AMENDED) A sensor according to claim 46 [or 47] in which the fibre is hydrogen loaded to increase the photosensitivity of the fibre.

49. A sensor according to claim 48 in which the hydrogen loaded fibre is annealed following fabrication of the grating structure to substantially remove any residual hydrogen from the fibre.

50. (AMENDED) A sensor according to [any of] claim[s] 1 [to 7 and 25 to 30] in which the grating portion comprises a surface-relief grating structure side-etched in an optical fibre.

51. (AMENDED) A sensor according to [any preceding] claim 25 in which the fibre grating sensor comprises a plurality of grating portions.

--54. (NEW) A sensor according to claim 25 in which the grating portion comprises a surface-relief grating structure side-etched in an optical fibre. --